

STEF GROUT WATERPROOFING

PRODUCT DESCRIPTION

Stef Grout specially blended from selected high quality performance cements, fillers, pigments and polymer-modified. Only water will be added to provide a creamy paste. When set, the hardened grout paste is mold and mildew resistant. Specially formulated for grouting all types of ceramic and dimensional stone tiles on walls and floors. It features innovative dustless technology producing less dust than ordinary cement grouts and is designed to promote cleaner working conditions and reduce mess.

USES

- For interior and exterior applications in both residential and commercial applications in wet and dry conditions.
- For floors and walls
- For application in submerged conditions (swimming pools, spas, water features and fountains) once fully cured (after 21 days)
- Suitable all tile types, brick, cement based terrazzo, porcelain and glass tile, natural stone tile, granite, ceramic, mosaic

CHARACTERISTICS / ADVANTAGES

- Non-shrink and No Cracks
- Non-Sag/ slump (thixotropic) application
- Water, mildew and mold resistant.
- Mixes with water only and easy to apply

FORM

Powder

COLOURS

Available in different colors (see color chart)

APPLICATION DETAILS CONSUMPTION / DOSAGE

One (1) square meter requires approx. 0,25 kg of grout powder, depending on type, size and spacing of tiles.

APPLICATION INSTRUCTIONS MIXING

Prepare about 0.3 liters of clean tap water in plastic pail. Add the 1 kg of Stef Grout gradually while mixing until a creamy paste is produced and allow to stand for 10 minutes. Do not use saline or salty water.

APPLICATION

Surface preparation before starting to grout, remove spacers and debris in grout joints and remove dust and dirt using a wet sponge. Do not leave water standing in joints. Apply the pasty grout to spaces between tiles (joints) diagonally using a sponge, or small piece of soft cloth. Work the grout paste with enough pressure into the joints and around the edges, filling them uniformly. When the residue on tiles begins to form a haze after (about 5 minutes), wipe a wet sponge using same diagonal strokes to the grout applied joints until the grout is flush with the tile surface. Wash the sponge, wring out as much water as possible, then toll the filled joints by lightly running the sponge along the tile grout lines or running the tip of gloved finger or a rounder piece of wood along the grout filled tile joints to level it off with the tiles. Wipe any remaining dry residue with a clean soft and dry cloth in order to reveal the tile surface with its true color and texture.

Place protective barriers or covering to protect newly grouted areas. Open to foot traffic only after at least 24 hours.

LIMITATION

Do not mix newly prepared grout paste with an old mix to extend the pot life. Freshly mixed grout in a pail remains useable up to one hour.

Do not use saline or salty water. Use only clean or clear tap water with no bacteria.

Do not use absorbent materials as mixing base or container.

Never use acid or other harsh chemicals to remove hardened grout on tile surfaces.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

HANDLING PRECAUTIONS

Avoid contact with skin & eyes.

Wear protective gloves and eye protection during work

If skin contact occurs, wash skin thoroughly

If in eyes open and flood with warm water. Seek medical attention without delay.

