





1-GROUP

11 487 €

• DIMENSIONS:

47 × 58 × 33 cm

• VOLTAGE/FREQUENCY/PHASE:

120 VAC, 50/60 Hz,
1.6 kW
220-240 VAC, 50/60 Hz,
2.1-2.4 kW

• ESSENTIAL FEATURES:

*Dual tank system with steam or brew tank priority
PID temperature control, adjustable in 0.1° increments
Electronic V3 grouphead rated to 1 million cycles
Commercial portafilter with 58-millimeter, 18-gram basket
Nanotech-coated precision shower screens
Wood handles and actuators
Hot water tap
Non-slip feet
Internal gear pump
Direct plumb only*



2-GROUP

25 275 €

• DIMENSIONS:

77.5 × 67.5 × 43.5 cm

• VOLTAGE/FREQUENCY/PHASE:

220-240 VAC, 50/60 Hz,

5.7-6.9 kW

380-415 V3N, 50/60 Hz,

5.7-6.9 kW

• ESSENTIAL FEATURES:

Independent brew tanks

PID temperature control, adjustable in 0.1° increments

Electronic V3 grouphead rated to 1 million cycles

Commercial portafilter with 58-millimeter, 18-gram basket

Nanotech-coated precision shower screens

Wood handles and actuators

Hot water tap with mixing valve

Non-slip feet

Shot mirror

External rotary pump



3-GROUP

31 998 €

• DIMENSIONS:

103 × 67.5 × 43.5 cm

• VOLTAGE/FREQUENCY/PHASE:

220-240 VAC, 50/60 Hz,

7.3-8.7 kW

380-415 V3N, 50/60 Hz,

7.3-8.7 kW

• ESSENTIAL FEATURES:

Independent brew tanks

PID temperature control, adjustable in 0.1° increments

Electronic V3 grouphead rated to 1 million cycles

Commercial portafilter with 58-millimeter, 18-gram basket

Nanotech-coated precision shower screens

Wood handles and actuators

Hot water tap with mixing valve

Non-slip feet

Shot mirror

External rotary pump



STEAM^{EP}

2-GROUP

36 396 

• DIMENSIONS:

86.5 × 70.5 × 42.5 cm

• VOLTAGE/FREQUENCY/PHASE:

220-240V, 50/60 hertz,
4.7 - 5.6 kW
380-415V3N, 50/60 hertz,
4.9 - 5.7 kW

• ESSENTIAL FEATURES:

Volumetric activation, two buttons with four programmable settings
Programmable HOLD 0-4 Seconds to pause water delivery before full pressure extraction.
Programmable Pre-Wet 0-4 sec
Centralized heads-up Barista Dashboard™
Intuitive, password-protected menus
Soft-Touch™ steam actuators and portafilters
PID-controlled independent brew tanks
Hot water mix valve
Massive work surface
Wing channels keep wires and hoses hidden
Anodized aluminum finish, body color
Powder coated matte black wings



STEAM^{EP}

3-GROUP

23 051 €

• DIMENSIONS:

110.5 × 70.5 × 42.5 cm

• VOLTAGE/FREQUENCY/PHASE:

220-240V, 50/60 hertz,
6.3 - 7.5 kW
380-415V3N, 50/60 hertz,
5.8 - 6.5 kW

• ESSENTIAL FEATURES:

Volumetric activation, two buttons with four programmable settings
Programmable HOLD 0-4 Seconds to pause water delivery before full pressure extraction.
Programmable Pre-Wet 0-4 sec
Centralized heads-up Barista Dashboard™
Intuitive, password-protected menus
Soft-Touch™ steam actuators and portafilters
PID-controlled independent brew tanks
Hot water mix valve
Massive work surface
Wing channels keep wires and hoses hidden
Anodized aluminum finish, body color
Powder coated matte black wings



STEAM^{LP}

2-GROUP

21 673 €

• DIMENSIONS:

86.5 × 70.5 × 42.5 cm

• VOLTAGE/FREQUENCY/PHASE:

220-240V, 50/60 hertz,
4.7 - 5.6 kW
380-415V3N, 50/60 hertz,
4.9 - 5.7 kW

• ESSENTIAL FEATURES:

Controllable independent pre-infusion programmable from 0-10 seconds
Post-infusion programmable by weight
Dual-volumetrics operation with two programmable doses per grouphead
1-5 second auto purge activated automatically or on demand
Pressure reducer to set your pre- and post-infusion pressure (line pressure or lower).
Quick push button to activate full manual versus volumetric mode
Advanced algorithm allows volumetric setting by weight
PID-controlled independent brew tanks
Electronic solenoid steam valves
Heads-up Barista Dashboard™ per group
Massive work surface
Wing channels keep wires & hoses hidden from view
Automatic shot lights
Adjustable drip tray
Mirror polished stainless steel body
Ink black wings and cup rail
Onyx Duratex™ actuators & Soft-Touch™ handles



STEAM^{LP}

3-GROUP

25 073 €

• DIMENSIONS:

110.5 × 70.5 × 42.5 cm

• VOLTAGE/FREQUENCY/PHASE:

220-240V, 50/60 hertz,
6.3 - 7.5 kW
380-415V3N, 50/60 hertz,
5.8 - 6.5 kW

• ESSENTIAL FEATURES:

Controllable independent pre-infusion programmable from 0-10 seconds
Post-infusion programmable by weight
Dual-volumetrics operation with two programmable doses per grouphead
1-5 second auto purge activated automatically or on demand
Pressure reducer to set your pre- and post-infusion pressure (line pressure or lower).
Quick push button to activate full manual versus volumetric mode
Advanced algorithm allows volumetric setting by weight
PID-controlled independent brew tanks
Electronic solenoid steam valves
Heads-up Barista Dashboard™ per group
Massive work surface
Wing channels keep wires & hoses hidden from view
Automatic shot lights
Adjustable drip tray
Mirror polished stainless steel body
Ink black wings and cup rail
Onyx Duratex™ actuators & Soft-Touch™ handles



STEAM^{LPX}

2-GROUP

23 038 €

• DIMENSIONS:

86.5 × 70.5 × 42.5 cm

• VOLTAGE/FREQUENCY/PHASE:

220-240V, 50/60 hertz,
4.7 - 5.6 kW
380-415V3N, 50/60 hertz,
4.9 - 5.7 kW

• ESSENTIAL FEATURES:

Controllable independent pre-infusion programmable from 0-10 seconds
Post-infusion programmable by weight
Dual-volumetrics operation with two programmable doses per grouphead
1-5 second auto purge activated automatically or on demand
Pressure reducer to set your pre- and postinfusion pressure (line pressure or lower).
Quick push button to activate full manual versus volumetric mode
Advanced algorithm allows volumetric setting by weight
PID-controlled independent brew tanks
Electronic solenoid steam valves
Heads-up Barista Dashboard™ per group
Massive work surface
Wing channels keep wires & hoses hidden from view
Automatic shot lights
Adjustable drip tray
Super polished chrome wings and brown Duratex™ cup rail
Brown Duratex™ actuators & Soft-Touch™ handles
Powder coated panels in 4 color options





STEAM^{LPX}

3-GROUP

26 425 

• DIMENSIONS:

110.5 × 70.5 × 42.5 cm

• VOLTAGE/FREQUENCY/PHASE:

220-240V, 50/60 hertz,
6.3 - 7.5 kW
380-415V3N, 50/60 hertz,
5.8 - 6.5 kW

• ESSENTIAL FEATURES:

Controllable independent pre-infusion programmable from 0-10 seconds
Post-infusion programmable by weight
Dual-volumetrics operation with two programmable doses per grouphead
1-5 second auto purge activated automatically or on demand
Pressure reducer to set your pre- and postinfusion pressure (line pressure or lower).
Quick push button to activate full manual versus volumetric mode
Advanced algorithm allows volumetric setting by weight
PID-controlled independent brew tanks
Electronic solenoid steam valves
Heads-up Barista Dashboard™ per group
Massive work surface
Wing channels keep wires & hoses hidden from view
Automatic shot lights
Adjustable drip tray
Super polished chrome wings and brown Duratex™ cup rail
Brown Duratex™ actuators & Soft-Touch™ handles
Powder coated panels in 4 color options



SLAYER

f slayerespresso.aze @slayerespresso.aze

SENSUM

OFFICIAL DISTRIBUTOR

2/29, Ahmad Rajabli, Narimanov district,
AZ1075, Baku, Azerbaijan

kamran.r@sensum.az
+994 55 208 84 79

g sensum.az f sensum.coffee @ sensum.coffee

