

PV 6000

PURE SINE WAVE SOLAR INVERTER



HYBRID INVERTER

Features

- Dual output for smart load management
- Maximum PV input current 27A
- Wide PV input voltage range 60VDC~450VDC
- Customizable status LED ring with RGB lights
- Touchable button with large 4.3" colored LCD
- Built-in Wifi or mobile monitoring (APP is available)
- Enhanced charging power



Supports USB On-the-Go function

- Data log event stored in the inverter.
- Reserved communication port (Rs485 , CAN-BUS or Rs232) for BMS
- Battery independent design
- Battery equalization extends lifecycle
- Built-in anti-dust kit



App Control
Option



Anti Dust
Filters



RGB
Lights



Dual AC
Output



Feed into
Grid



USB
Option



Built In
Wifi



Communication
Ports



Touchable Button
Colored LCD



Scan for Download
PDF Data Sheet

SIGNATURE Series



Specification :

MODEL	Signature Series VM IV 6KW TWIN
RATED POWER	6000VA/6000W
INPUT	
Voltage	230 VAC
Selectable Voltage Range	170-280 VAC (For Personal Computers) 90-280 VAC (For Home Appliances)
Frequency Range	50 Hz/60 Hz (Auto sensing)
OUTPUT	
AC Voltage Regulation (Batt. Mode)	230VAC \pm 10%
Surge Power	12000VA
Efficiency (Peak)	90% ~ 93%
Transfer Time	10 ms (For Personal Computers) 20 ms (For Home Appliances)
Waveform	Pure sine wave
BATTERY	
Battery Voltage	48 VDC
Floating Charge Voltage	54 VDC
Overcharge Protection	63 VDC
SOLAR CHARGER & AC CHARGER	
Solar Charger type	MPPT
Maximum PV Array Power	6000W
MPP Range @ Operating Voltage	60 ~ 450 VDC
Maximum PV Array Open Circuit Voltage	500 VDC
Maximum PV Input Current	27A
Maximum Solar Charge Current	120A
Maximum AC Charge Current	100A
Maximum Charge Current	120A
PHYSICAL	
Dimension, D x W x H (mm)	119 x 313.6 x 457.5
Net Weight (kgs)	12
Communication Interface	USB/RS232/RS485/WiFi/Dry-contact
OPERATING ENVIRONMENT	
Humidity	5% to 95% Relative Humidity (Non-condensing)
Operating Temperature	-10°C to 50°C
Storage Temperature	-15°C to 60°C

روشن جدید پاکستان