



mh2u.com.my

UP TO SPEED

150PPM



## Nested Filling and Stoppering Machine (HFN250)

### Features

- DATA Integrity comply with FDA 21 CFR Part 11
- SCADA Ready & Remote Assistant.
- Full Servo Driven with ONE Touch Mechanical Adjustment
- Precision Seal-less Rotary Piston Pump (SUS316L & Autoclavable).
- Programmable filling profile to achieve surface filling & drip-free.
- Vacuum Stoppering system to minimize entrapped air during rubber insertion.
- "Trackless" Rubber Stopper feeding to eliminate jamming at the track.

### Performance

Production Speed	: 60ppm / 150ppm
Filling Accuracy	: + / - 1%
Filling Range	: Vial (2R-20R) Syringe (1ml-20ml) Cartridge (3ml-20ml)
Electricity	: 5KW @380-415VAC
Air Supply	: 50LPM @6bar
Machine Dimension	: L1400mm x W1800mm x H1900mm (HFN120) L1400mm x W1800mm x H1900mm (HFN250)

Note: Optional 6 Axis Robotic Statistical or 100% In-Process Weight Check, oRABS, cRABS, Isolator Barrier System, Load Cell Filling Buffer Tank, Gas Flushing, CIP/SIP System Filling Pump, Vacuum Filling, Upstream De-Bag, De-Lid & Liner can be add on.