

PRODUCT DESCRIPTION:

STEF JOINT COMPOUND is a high quality, asbestos-free, ready mixed all purpose compound for filling joints and holes in cement and drywall construction.

ADVANTAGES:

- lightweight
- ready to use
- excellent adhesion and workability
- very little shrinkage; thus minimum cracking
- easier sanding

LIMITATIONS:

STEF JOINT COMPOUND is for interior applications only. Ambient, surface and material temperatures must be above 13°C. (55°F) during application and for minimum 48 hours after application.

MIXING PROCEDURE:

JOINT COMPOUND

ALL-PURPOSE CEMENT AND DRYWALL COMPOUND

APPLICATION:

Cement and Drywall surfaces must be clean and sound, free of weak and powdery surfaces, dust, dirt, oil, grease and any other deleterious materials detrimental to a positive bond.

Deteriorating, weak, powdering sections of drywall must be replaced.

Thinning the compound is not recommended. However if job conditions require a thinner compound, add potable water, up to maximum 1 quart per gallon of compound and mix.

TECHNICAL DATA

Physical Properties:

Product type:	Ready mixed, non cementitious calcium carbonate
Appearance:	Thick white paste
Toxicity:	Non-toxic
Pot life:	24 hrs. after opening of box

Performance Characteristics:

Mixing ratio:	No mixing required ready mixed. Small amounts of water can be added to desired consistency.
Coverage:	Coverage will vary according to texture method of application.
Average consumption:	1 box per 10.2 m2 (500 ft2) drywall taped
Substrate requirement:	Clean solid drywall

Mix compound in original container prior to use. DO NOT SUBSTITUTE NOR COMPENSATE **STEF JOINT COMPOUND** WITH WATER OR OTHER ADDITIVES. Discard all materials which have begun to harden.

Allow compound to dry thoroughly between coats.

CLEAN UP:

Clean all tools promptly after each use with water. Do not allow mixes to dry on tools.

STORAGE:

Store **STEF JOINT COMPOUND** in a dry, vented, waterproof location, stacked off the ground with ambient temperatures above 13°C (55°F).

Keep materials dry, protected from rapid temperature changes, dampness and moisture and away from direct sunlight.

KEEP FROM FREEZING.

PACKAGING: STEF JOINT COMPOUND is readily available in 17 Lt and 4 litres pails. It is available in white



Stef Coating

Version : 200 858

819 820-1188 | 1 877 316-6388 | 4365, Robitaille Street, Sherbrooke, QC J1L 2K2 | info@texnov.com | www.texnov.com