



HYBRID INVERTER

Features

- Dual output for smart load management
- Maximum PV input current 27A
- Wide PV input voltage range 60VDC~450VDC
- Customizable status LED ring with RGB lights
- Touchable button with large 4.3" colored LCD
- Built-in Wifi for mobile monitoring (Android/iOS App Available)
- Built-in anti-dust kit

- Data log event stored in the inverter
- Reserved communication port (RS485, CAN-BUS or RS232) for BMS
- Battery independent design
- Battery equalization extends lifecycle
- Enhanced charging power
- Supports USB On-the-Go function



App Control
Option



RGB
Lights



Dual AC
Output



Anti Dust
Filters



Feed into
Grid



USB
Option



Built In
Wifi




Touchable Button
Colored LCD



Communication
Ports



Scan for Download
PDF Data Sheet



SIGNATURE Series



Specification :

MODEL	Signature Series VM IV 4KW TWIN
RATED POWER	4000VA/4000W
INPUT	
Voltage	230 VAC
Selectable Voltage Range	170-280 VAC (For Personal Computers) 90-280 VAC (For Home Appliances)
Frequency Range	50 Hz/60 Hz (Auto sensing)
OUTPUT	
AC Voltage Regulation (Batt. Mode)	230VAC $\pm$ 10%
Surge Power	8000VA
Efficiency (Peak)	90% ~ 93%
Transfer Time	10 ms (For Personal Computers) 20 ms (For Home Appliances)
Waveform	Pure sine wave
BATTERY	
Battery Voltage	24 VDC
Floating Charge Voltage	27 VDC
Overcharge Protection	33 VDC
SOLAR CHARGER & AC CHARGER	
Solar Charger type	MPPT
Maximum PV Array Power	5000W
MPPT Range @ Operating Voltage	60 ~ 450 VDC
Maximum PV Array Open Circuit Voltage	500 VDC
Maximum PV Input Current	27A
Maximum Solar Charge Current	120A
Maximum AC Charge Current	100A
Maximum Charge Current	120A
PHYSICAL	
Dimension, D x W x H (mm)	119 x 313.6 x 457.5
Net Weight (kgs)	10
Communication Interface	USB/RS232/RS485/WiFi/Dry-contact
OPERATING ENVIRONMENT	
Humidity	5% to 95% Relative Humidity (Non-condensing)
Operating Temperature	-10°C to 50°C
Storage Temperature	-15°C to 60°C

روشن جدید پاکستان